CESSNA 185 CHECK LIST

BEFORE ENGINE START

- 1. Preflight inspection Complete
- 2. Seatbelts Fastened
- 3. Fuel shutoff valve On
- 4. Avionics power Off
- 5. Autopilot Off
- 6. Circuit breakers Check
- 7. Cowl flaps **Open**

ENGINE START

- 1. Mixture Rich
- 2. Prop High RPM
- 3. Master switch On
- 4. Fuel pump *On*
- 6. Throttle Full then close (2 seconds)
- 7. Prop Clear
- 8. Brakes Set
- 9. Ignition switch **Start**
- 10. Throttle Advance until engine starts
- 11. Throttle Reduce to 1000 RPM
- 12. Oil pressure Check
- 13. Nav lights On (night)

BEFORE TAKEOFF

- 1. Doors **Locked**
- 2. Controls Free and correct
- 3. Instruments Check and Set
- 4. Fuel shutoff valve **On**
- 5. Fuel selector Both
- 6. Fuel quantity *Check*
- 7. Mixture *Rich* (or lean for elevation)
- 8. Trim *Set*
- 9. Cowl flaps Open
- 10. Runup

Prop: 1700 RPM

Magnetos: right/left (150 max drop)

Prop: cycle
Suction: check
Ammeter: check

- 11. Radios Set
- 12. Autopilot Off
- 13. Transponder ALT
- 14. Strobes **On** (night)
- 15. Flaps 20° or 30°

TAKEOFF

1. Initial climb: Full power

85 KIAS

2. Obstacles cleared: 25"/2500 RPM

100 KIAS Flaps up

BEFORE LANDING

- 1. Cowl flaps Closed
- 2. Seat belts Fastened
- 3. Fuel selector **Both**
- 4. Mixture Rich
- 5. Prop High RPM
- 6. Flaps 10° to 40°

7. Speed: **Downwind** 80 KIAS **Final** 70 KIAS **Short field** 60 KIAS

AFTER LANDING

- 1. Flaps *Up*
- 2. Cowl flaps Open
- 3. Trim Centered

SHUTDOWN

- 1. Avionics power Off
- 2. Mixture *Idle cutoff*
- 3. Mags Off after prop stops
- 4. Master Off

<u>SPEEDS</u>		KIAS
Best	(3350 lb)	75
glide	(1950 lb)	58
Va	(3350 lb)	118
	(1950 lb)	90
Vx	(flaps 10)	57
	(flaps 20)	47
	(flaps 30)	37
Vy	(sea level)	88
·	(10000 ft)	82

EMERGENCY LANDING

- 1. **TRIM** for 75 KIAS
- 2. **CHOOSE** a field & **TURN** to it
- 3. **TROUBLESHOOT** if time permits
 - fuel selector, primer
 - mixture, magnetos
 - fuel and oil pressure
 - try engine restart
- 4. **COMMUNICATE** if time permits
 - Mayday: on 121.5 (who, where)
 - Squawk: 7700
- 5. LANDING
 - Seatbelts SECURE
 - Fuel selector OFF
 - Mixture IDLE CUTOFF
 - Magnetos/Master OFF
 - Door UNLATCHED
 - Flaps 40°